

FRED C. GILBERT CO.

106 NORRIS ROAD
BAKERSFIELD, CA. 93308
661-399-9569
www.fcgilbert.com

POLYMER PUMP™ POLYMER INJECTOR PUMP

THE HEAVY DUTY SOLUTION



www.polymerpump.com

STANDARD UNIT FEATURES INCLUDE:

- *Rated from 0 to .9 GPM, 75 PSI (volume based on viscosity of water)*
- *No check valves to clog, low maintenance*
- *Great for polymer injection, polymer mixing & polymer recirculation*
- *Manual Variable speed from 0 to 360 rpm through use of Nema4 rated controller*
- *Made for Continuous Heavy Duty Use*
- *Capable of 40,000 CPS and higher (flooded suction)*
- *1/2 HP TEFC SCR rated motor - 115 or 230 volt single phase input power*
- *All Stainless Steel / Buna-N® wetted parts*
- *1" FNPT or 1" flanged inlet x 3/4" FNPT outlet*
- *Standard unit Dimensions are 13" wide x 26" long x 17.75" tall / 80 pounds shipping weight*
- *Motor & Drive may be rotated in 90 degree increments for ease of plumbing & wiring*
- *Many other options are available including Viton® trim, 4-20 MA Input Signal for Automatic Proportioning, On Board Make Down System (using motionless mixer & adjustable rotameter), Explosion Proof drive, 3 Phase Motor, High Pressure Options, Water Flushing System & Slower Speed / Lower Output Units.*